

TyloSensor



BENEFITS



RAPID

Results in 6 minutes.



SENSITIVE

Limit of detection below EU MRLs.



SPECIFIC

Detection of Tylosin.



RELIABLE AND ROBUST



USER-FRIENDLY

Easily performed on site or in lab.



COST-EFFECTIVE

RESULTS

Visual interpretation of the result obtained by comparing the intensity of each test line with the control (CTRL) line.



An instrumental reading is also possible with the ReadSensor device.

SENSITIVITY

COMPOUNDS	LIMITS OF DETECTION (PPB)	
	KIT049	EU MRL
Tylosin	5 - 10	50



HOW TO USE





Place the vial to heating block




Close and push "START"



Place dipstick to Heatsensor





TyloSensor

PRODUCTS REFERENCES

KIT049

TYLOSENSOR MK MRL - 96 PC

APP032
HEATSENSOR DUO
APP052
HEATSENSOR OCTO



Reseller

APP038
READSENSOR ESE SMALL CASE
APP039
READSENSOR ESE FULL CASE





Liège Science Park Allée de la Cense-Rouge, 98 B-4102 Ougrée (Liège) BELGIUM

www.unisensor.be

Phone +32 4 252 66 02 Fax +32 4 252 90 55 info@unisensor.be

