

# DISRUPTOR GENIE® Cell Disruptor

**NEW  
IMPROVED  
DESIGN ON  
ALL MODELS**



**ANALOG**



**Unique  
multi-directional  
action for  
simultaneous  
agitation and  
vortexing.**



**DIGITAL**



**Disruptor Beads™**

U.S. Pats. 5,707,861  
4,781,487

- Rapid hands-free disruption of up to 12 microtubes (1.5ml or 2.0ml) with NEW Universal Microtube Holder
- Timer for speed up to 15 minutes for Analog model, up to 99 minutes for Digital model or continuous for both models
- Suitable for use in cold rooms or incubators
- Less costly than ultrasonic units or homogenizers
- Use with Disruptor Beads™, made from spherical lead free soda lime glass, available in two sizes
- Disruptor Beads are used with any Disruptor Genie or TurboMix™ attachment for Vortex-Genie® 2 family
- Digital model is ideal for accurate, reproducible, repeatable results. Features adjustable speed and speed alarm.

### Disruptor Genie and Disruptor Beads applications:

- Disruption of bacterial cultures for nucleic acid isolation and downstream processing
- Grinding plant tissue for DNA extractions
- Preparation of cell lysates from yeast or fungi
- Rapid resuspension of pellets
- Dissolution of chemical substances

### Ordering Information

Catalog No.	Description
SI-D238	Disruptor Genie, 120V
SI-D248	Disruptor Genie, 230V, No Plug
SI-D258	Disruptor Genie, 230V, Euro Plug
SI-D268	Disruptor Genie, 230V, British Plug
SI-D278	Disruptor Genie, 230V, Swiss Plug
SI-D298	Disruptor Genie, 240V, Australian Plug
SI-D288	Disruptor Genie, 100V
SI-DD38	Digital Disruptor Genie, 120V
SI-DD48	Digital Disruptor Genie, 230V, No Plug
SI-DD58	Digital Disruptor Genie, 230V, Euro Plug
SI-DD68	Digital Disruptor Genie, 230V, British Plug
SI-DD78	Digital Disruptor Genie, 230V, Swiss Plug
SI-DD98	Digital Disruptor Genie, 240V, Australian Plug
SI-DD88	Digital Disruptor Genie, 100V
SI-BG01	Disruptor Beads, 0.1mm, 375g (8 fl. oz.)
SI-BG05	Disruptor Beads, 0.5mm, 375g (8 fl. oz.)

### Specifications

Disruptor Genie	
Weight	4.3 Kg (9.5 lb)
Base Dimensions (D x W x H)	165 x 122 x 190mm 6.5 x 4.8 x 7.5in
Time range (Analog)	0 - 15 minutes or continuous
Time range (Digital)	0 - 99 minutes or continuous
Capacity	Up to 12 - 1.5ml or 2.0ml microtubes (additional holders sold separately, tubes not supplied)
Speed (Analog)	3000 RPM (2850 for 50Hz models)
Speed (Digital)	1000-3000 RPM (2850 for 50Hz models)
Speed Alarm (Digital)	On/Off, Adjustable
Disruptor Beads	
Bead Sizes	0.1mm diameter beads for bacteria 0.5mm diameter beads for yeast
Weight	375 grams (8 fl. oz.)

ETL ETL Listed Conforms to UL Std. 3101-1  
ETL ETL Listed Certified to CAN/CSA C22.2  
(Analog Only)

CE (Both Models)



**Home of the Multi-Task Genie™ Family**  
80 Orville Drive, Suite 102  
Bohemia, NY 11716 U.S.A.  
Phone: (631) 567-4700 • Fax: (631) 567-5896  
Toll Free: 888-850-6208  
Customer Service: [custsvc@scientificindustries.com](mailto:custsvc@scientificindustries.com)  
[scientificindustries.com](http://scientificindustries.com)

© 2014 Scientific Industries, Inc. LTP0048 Rev. D

### Reseller

**im** n.v. International Medical Products S.A.  
Waverssesteeweg 1110/7 Chaussée de Wavre  
OUDERGEM 1160 AUDERGEM - BELGIUM  
T: +32 (0)2 660 50 75 - F: +32 (0)2 660 20 98  
[www.intermed.be](http://www.intermed.be) - [info@intermed.be](mailto:info@intermed.be)